



MATERIAL SAFETY DATA SHEET

1. Chemical Product & Company Data

Product name Un Do (Vanilla)	
Manufacturer: Il Rep-Z, Inc. 4660 Elizabeth St. Coraopolis, PA 15108 Telephone: 1-412-264-8340	Supplier:

2. Hazardous Ingredients

Name	CAS #	UN #	% by volume
Ethyl Alcohol	64-17-5		60-100
Methyl Isobutyl Ketone	108-10-1		1-5
Fragrance - Aromatics (aldehydes, esters & ketones) and alcohols	n. av.		5-10

3. Hazards Identification

Emergency Overview

Flammable liquid Skin and eye irritant

NOTE: Hazard information is based on the characteristics of the components of this mixture.

Ingestion - may cause abdominal discomfort, drowsiness or unconsciousness may occur.

Inhalation - low concentration of the vapor may cause irritation of the respiratory tract. High concentrations may cause headache and drowsiness.

Eye contact - causes eye irritation.

Skin contact - prolonged contact may cause irritation drying and cracking of the skin.

4. First Aid

Ingestion - If patient is conscious give two glasses of water. Induce vomiting. Seek medical attention immediately.

Inhalation - Remove to fresh air. Administer artificial respiration if not breathing. Obtain medical attention.

Eye contact - Flush eyes with water for 15 minutes. Seek immediate medical attention.

Skin contact - Remove contaminated clothing. Wash skin with soap and water. Obtain medical attention if irritation persists.

Un Do (Vanilla)

5. Fire Fighting Measures

Flammability Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	If yes, under which conditions ? Flammable liquid. Potential fire hazard when exposed to excessive heat flame or other sources of ignition.		
Flashpoint (°C) 10°C TCC	Upper flammable limit % by volume 21.2 @ 64 °C	Lower flammable limit % by volume 3.5 @ 25°C	
Autoignition temperature (°C) > 404 °C	Hazardous combustion products Carbon monoxide and/or carbon dioxide		
Explosion data: n.ap.			
Means of extinction: Apply alcohol type or all purpose foam for large fires. Use dry chemical media or carbon dioxide extinguishers for small fires. SCBA and bunker gear for fire department personnel			

6. Accidental Release Measures

<p>Eliminate all sources of ignition</p> <p>Wear personal protective equipment</p> <p>Do not allow spill to reach watercourse or sewers</p> <p>Contain spill with absorbent mats or booms or inert materials such as sand. Material should be readily available in the workplace.</p> <p>Collect and store waste materials in suitable containers for disposal i.e. metal drums</p>

7. Handling & Storage

<p>Use non sparking tools and explosion proof mechanical equipment when working with this liquid i.e. pumps and sprayers</p> <p>Extinguish all sources of ignition in the work area. If the product is stored in metal containers the container must be grounded and bonded prior to dispensing the liquid. To prevent vapor escaping to the atmosphere keep all containers closed or covered. The product should be stored in a separate room equipped for flammable liquid storage or small volumes may be stored in a flammable liquid cabinet. Check local Health and Safety Authority for the volume limits in these situations. Eyewash stations are required in the workplace. If eye irritation is encountered the use of a full facepiece respirator is recommended. Mechanical ventilation is recommended in enclosed workspaces. Area should be evacuated of all non essential personnel prior to application of product.</p>
--

8. Exposure Controls & Personal Protection

Personal Protective Equipment				
Gloves natural rubber	Respirator NIOSH TC-23C organic vapor or equivalent	Eye goggles or full face respirator		
Footwear n. ap.	Clothing coveralls or equivalent	Other n. ap.		
Exposure Guidelines				
* none established for product *				
	OSHA		ACGIH	
	TWA	STEL	TWA	STEL
Ethyl alcohol	1000 ppm		1000 ppm	
Methyl isobutyl ketone	50 ppm	75ppm	50 ppm	75 ppm

Un Do (Vanilla)

9. Physical & Chemical Properties

Physical state liquid	Odor and appearance Clear pale yellow color, almond odor		
Odor threshold (ppm) Ethanol 10 ppm Methyl isobutyl ketone 3 ppm	Vapor pressure (mm Hg) 40	Vapor density (Air=1) 1.6	
Evaporation rate (butyl acetate = 1) 3.9	Boiling point (°C) 79	Freezing point (°C) n. av.	
pH n. av.	Specific gravity 0.83	Coefficient water/oil distribution n. av.	
Solubility in water n. av.	Viscosity n. av.	% Volatiles (by weight) n. av.	

10. Stability & Reactivity

Chemical stability Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	If no, under which conditions ?		
Incompatibility with other substances Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	If yes, under which conditions ? avoid contact with strong oxidizing agents, inorganic acids		
Reactivity, and under what conditions? stable under normal conditions			
Hazardous decomposition products Carbon monoxide and/or carbon dioxide as combustion by-products			

11. Toxicological Information

Route of Entry			
Skin contact <input checked="" type="checkbox"/>	Skin absorption <input type="checkbox"/>	Eye contact <input checked="" type="checkbox"/>	Inhalation <input checked="" type="checkbox"/> Ingestion <input checked="" type="checkbox"/>
No toxicity studies have been conducted for this product.			
Carcinogenicity no	Mutagenicity no	Teratogenicity no	Reproductive toxicity no
Synergistic products no	Sensitization no	Neurotoxicity no	Target organs skin and eyes

12. Ecological Information

n. av.

13. Disposal Considerations

Do not dispose of product in storm or sanitary sewer systems.
 Do not allow discharge into groundwater or a watercourse.
 If product is to be disposed of, contact a licensed or registered waste disposal firm to incinerate the product.

14. Transport Information

Shipping name FLAMMABLE LIQUIDS, N.O.S.
 Hazard class 3 (Packing Group II)
 UN Identification # 1993
 US Domestic shipments up to 5 liters (1.3 gallons) per bottle
 Consumer Commodity ORM-D for ground shipments
 Consumer Commodity ORM-D-AIR for air shipments

15. Regulatory Information

This material safety data sheet has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Hazardous Products Act (Can.) and the Controlled Products Regulations (Can.) This product has been classified in accordance with the hazard criteria of the CPR (Can.) and the MSDS contains all the information required by the CPR (Can.).

This product is classed as a **flammable liquid and as a skin and eye irritant** - 29 CFR 1910.1200 and Controlled Products Regulations (Can.)

WHMIS classification **B2 D2B**

This product is not subject to the reporting requirements of Section 313 of Title III of Superfund Amendments and Reauthorization Act (SARA) 1986 and 40 CFR part 372

16. Other Information

This product is a commercial cleaning and deodorizing chemical.

For chemical emergency during transportation call INFOTRAC (US) **1-800-535-5053** (INT'L) **1-352-323-3500**

Prepared by: II Rep-Z, Inc., Coraopolis, PA / Cliff Zlotnik

Phone No: 1-412-264-8340

Date March 9, 2004

abbreviations

n. av. = not available n. ap. = not applicable ppm = parts per million mm Hg = millimeters of Mercury
 cs = centistokes PMCC = Pensky Martens Closed Cup TCC = Tagliabue Closed Cup COC = Cleveland Open Cup
 TWA = time weighted average STEL = short term exposure limit LD= lethal dose LC=lethal concentration