



# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: FABRIC PRESPRAY  
CU65

## SECTION 1: PRODUCT INFORMATION

Distributed By: Bridgepoint Systems, 4282 W 590 W, Salt Lake City, Utah 84123  
Company Phone Number: 801-261-1282  
Emergency Phone Number: 1-800-535-5053 (Infotrac)  
Date Prepared: 02/01/2011

Hazard Rating (Zero=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)  
Fire: 0 Health: 1 Reactivity: 0

## SECTION 2: INGREDIENTS

PRINCIPLE HAZARDOUS INGREDIENTS :      OSHA PEL

Surfactant mixture      N/E

Diethylene Glycol buytl ether (Cas # 112-34-5)      N/E

## SECTION 3: PHYSICAL DATA

Boiling Point (°F).....349°F	Specific Gravity(H <sub>2</sub> O=1).....1.016
Vapor Pressure (mmHg.).....N/D	Percent Volatile by Volume... N/D
Vapor Density (AIR=1)..... N/D	PH (1% Solution).....8
Solubility in Water..... N/D	

Appearance & Odor.....Clear liquid with mint scent

## SECTION 4: FIRE, EXPLOSION & REACTIVITY DATA

**Flash Point:** >212°F

**Extinguishing Media:** Product is not flammable. Use water, carbon dioxide, dry powder or other media appropriate for materials actually involved in fire.

**Special Fire Fighting Procedures:** Wear self-contained breathing apparatus and full protective clothing

**Unusual Fire and Explosion Hazards:** None

**Stability:** Stable

**Chemical Incompatibility:** Avoid strong oxidizing or alkaline agents

**Hazardous Decomposition or Byproducts:** During a fire, smoke may contain the original material in addition to unidentified toxic and/or irritating compounds. Hazardous combustion products may include and are not limited to carbon dioxide and carbon monoxide

**Hazardous Polymerization:** Will not occur

**Conditions to Avoid:** Only those listed under Chemical Incompatibility

