



Du Pont
Material Safety Data Sheet

DuPont (TM) StoneTech (R) Professional Impregnator Pro (TM)
6608CR Revised 5-FEB-2009

Substance ID :130000027527

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Company Identification

MANUFACTURER/DISTRIBUTOR

DuPont StoneTech (R) Professional
370 North Wiget Lane, Suite 200
Walnut Creek, CA 94598

PHONE NUMBERS

Product Information : 800-441-7515/Outside US: 302-774-1000
Transport Emergency : CHEMTREC: 800-424-9300/Outside US:
703-527-3887
Medical Emergency : 800-441-3637/Outside US: 302-774-1000

COMPOSITION/INFORMATION ON INGREDIENTS

Components

Table with 3 columns: Material, CAS Number, %

HAZARDS IDENTIFICATION

Potential Health Effects

Inhalation may cause respiratory irritation with headache,
dizziness, nausea, or unconsciousness.
Skin contact may cause mild irritation.
Eye contact may cause mild irritation.
Ingestion may irritate stomach and intestines. May be
aspirated into lungs if swallowed, resulting in pulmonary
edema and chemical pneumonitis. Harmful or fatal if
swallowed.

Carcinogenicity Information

None of the components present in this material at concentrations
equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH
as a carcinogen.

Du Pont
Material Safety Data Sheet

FIRST AID MEASURES

First Aid

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. DO NOT GIVE ANYTHING TO DRINK. Call a physician immediately. Never give anything by mouth to an unconscious person.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point : 108 F (42 C)
Method : Closed Cup.

Combustible liquid.

Extinguishing Media

Water, Foam, Dry Chemical, CO2.

Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate

Du Pont
Material Safety Data Sheet

PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Wear self-contained breathing apparatus (SCBA) and full protective gear.

Initial Containment

Dike spill.

Spill Clean Up

Soak up with sawdust, sand, oil dry or other absorbent material. Shovel or sweep up.

HANDLING AND STORAGE

Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. Wash clothing after use.

Handling (Physical Aspects)

Keep container tightly closed.

Storage

Store in a cool, dry place.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use only with adequate ventilation.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

PROTECTIVE CLOTHING

Where there is potential for skin contact, have available and wear as appropriate impervious gloves, apron or smock.

Du Pont
Material Safety Data Sheet

Exposure Guidelines

Applicable Exposure Limits

Butyl Acetate
PEL (OSHA) : 150 ppm, 710 mg/m³, 8 Hr. TWA
TLV (ACGIH) : 150 ppm, 8 Hr. TWA
AEL * (DuPont) : None Established

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

Exposure Guideline Comments

Aliphatic Hydrocarbon
TLV* (ACGIH) : 200 ppm

*Provided by Chevron Phillips

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Evaporation Rate : <1 (Butyl Acetate=1.0)
Solubility in Water : Negligible
Boiling Point : >300 F (>149 C)
Odor : Hydrocarbon (mild).
Form : Liquid.
Color : Colorless.
Specific Gravity : 0.75 25 C (77 F)

STABILITY AND REACTIVITY

Chemical Stability

Stable.

Incompatibility with Other Materials

Incompatible with oxygen, strong oxidizing agents.

Decomposition

Thermal decomposition may produce carbon monoxide, carbon dioxide and hydrogen fluoride.

Polymerization

Polymerization will not occur.

DISPOSAL CONSIDERATIONS

Du Pont
Material Safety Data Sheet

Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

TRANSPORTATION INFORMATION

Shipping Information

DOT: Not Regulated by DOT in packages with a capacity of less than 119 gallons.

IMDG:

For 5 gal. and 55 gal. package:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.
Hazard Class : 3
UN Number : 3295
Packing Group : III
Label : Flammable Liquid

For 2 Oz., 1 Pint, 1 Quart, and 1 Gal.:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.
Hazard Class : 3
UN Number : 3295
Packing Group : III
Label : Flammable Liquid
Special Instructions : Limited Quantity

IATA:

For 5 gal. and 55 gal. package:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.
Hazard Class : 3
UN Number : 3295
Packing Group : III
Label : Flammable Liquid

For 1 Quart and 1 Gal.:

Proper Shipping Name : Hydrocarbon Liquid, N.O.S.
Hazard Class : 3
UN Number : 3295
Packing Group : III
Label : Flammable Liquid
Special Instructions : Limited Quantity

For 2 Oz. and 1 Pint:

Du Pont
Material Safety Data Sheet

Proper Shipping Name : Consumer Commodity
Hazard Class : 9
UN Number : ID 8000
Label : Miscellaneous

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : In compliance with TSCA Inventory requirements for commercial purposes.

OTHER INFORMATION

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsible for MSDS : MSDS Coordinator
> : DuPont Chemical Solutions Enterprise
Address : Wilmington, DE 19898
Telephone : (800) 441-7515

Indicates updated section.

End of MSDS